

PIT BULL® 14 PRODUCTIVITY PACKAGE

1" IPS - 4" DIPS (32MM - 110MM)



MADE FOR

UNDERGROUND
CONSTRUCTION



ABOUT PIT BULL 14 WITH PRODUCTIVITY PACKAGE

For a compact, lightweight, rugged and reliable fusion machine for 1" IPS to 4" DIPS (32mm to 110mm) pipe, look no further than the Pit Bull® 14.

This hand-operated fusion machine incorporates McElroy's patented Centerline Guidance System and is designed to butt fuse tees, ells, and other fittings with consistent and high-quality results. Its reversible jaws, clamp knobs, levers, and facer allow the operator to fuse from either side of the machine while a semi-automatic locking mechanism maintains force during the cooling cycle.

The Pit Bull 14 Productivity Package includes a Pit Bull 14 fusion machine, Manual Fusion Machine Stand and two PolyPorters®, designed for the contractor or operator who wants to save time and money by combining these labor-saving machines into one cost-efficient package.

ADDITIONAL IMAGES



STANDARD FEATURES

- ✓ Hand-operated
- ✓ Lightweight and durable
- ✓ 15-to-1 mechanical advantage
- ✓ Patented Centerline Guidance System for equal distribution of force around the joint
- ✓ Semi-automatic locking mechanism to maintain force during the cooling cycle
- ✓ Hard-anodized clamp knobs to minimize force required to clamp and round pipe
- ✓ Serrated jaws and inserts keep pipe from slipping during fusion
- ✓ Electric facer design
- ✓ Reversible jaws, clamp knobs, levers and facer allow operator to fuse from either side of the machine
- ✓ Thrust-bearing equipped clamp knobs to minimize torque required to clamp and round the pipe
- ✓ Thermostatically-controlled heater to provide constant fusion temperature
- ✓ ISO-compliant industrial Teflon-coated heater plates
- ✓ Compact and durable



SEE SECOND PAGE FOR DETAILED SPECIFICATIONS



PIT BULL® 14 PRODUCTIVITY PACKAGE

1" IPS - 4" DIPS (32MM - 110MM)

SPECIFICATIONS

MODELS		POWER			MACHINE DIMENSIONS	
A441501	120V	Minimum Power Requirements	3 kW		Machine Length	15.5" (393.7mm)
A441502	240V				Machine Width	16.5" (419.1mm)
		240V Heater	220-240V, 1,200 Watts, 50 Hz, 1 Ph		Machine Height	31.8" (807.7mm)
		120V Heater	100-120V, 1,200 Watts, 60 Hz, 1 Ph		SHIPPING DIMENSIONS	
WEIGHTS		240V Facer	220-240V, 50 / 60 Hz, 1 Ph, 3.5 Amps		Length	62" (1,574.8 mm)
Carriage	35 lbs. (15.9 Kg)	120V Facer	100-120V, 50 / 60 Hz, 1 Ph, 7 Amps		Width	40" (1,016 mm)
Heater	10 lbs. (4.5 Kg)				Height	40" (1,016 mm)
Facer	21.6 lbs. (9.8 Kg)				INCLUDES	
Shipping Weight	370 lbs. (167.8 Kg)	120V Heater Plug type	NEMA 5-15P			
		240V Heater Plug type	NEMA 6-15P			
		120V Facer Plug type	NEMA 5-15P			
		240V Facer Plug type	NEMA 6-15P		Pit Bull 14 fusion machine, manual fusion machine stand , and two PolyPorters® .	