

PIT BULL® 26 6" DIPS MAX PIPE SIZE

2" IPS - 6" DIPS (63MM - 180MM)



MADE FOR
UNDERGROUND
CONSTRUCTION



STANDARD FEATURES

- ✓ Hand-operated
- ✓ Compact and Durable
- ✓ 17-to-1 mechanical advantage
- ✓ Patented Centerline Guidance System for equal distribution of force around the joint
- ✓ Reversible jaws, clamp knobs, levers and facer allow operator to fuse from either side of the machine
- ✓ Thrust bearing equipped clamp knobs to minimize torque required to clamp and round the pipe
- ✓ Semi-automatic locking cam to maintain force during the cooling cycle
- ✓ Hard anodized aluminum wear surfaces for corrosion resistance
- ✓ Conventional facer design features ball-bearing construction and gear drive for long life
- ✓ Serrated jaws and inserts keep pipe from slipping during fusion
- ✓ Narrow clamp design for precise pipe alignment
- ✓ ISO-compliant industrial Teflon-coated heater plates
- ✓ Thermostatically-controlled heater to provide constant fusion temperature



ABOUT PIT BULL 26

McElroy's Pit Bull® line has cemented itself as the industry standard machine for in-ditch manual fusion.

The Pit Bull 26 is a compact, lightweight, rugged, and reliable fusion machine designed to fuse pipe sizes from 2" IPS to 6" DIPS and 63mm to 180mm.

This manual machine incorporates McElroy's patented Centerline Guidance System and is designed to butt fuse tees, ells, and other fittings with consistent and high-quality results. Its reversible jaws, clamp knobs, levers, and facer allow the operator to fuse from either side of the machine while a semi-automatic locking mechanism maintains force during the cooling cycle. For an added level of convenience, the Pit Bull 26 includes an electric facer with balance point handle for fast facing of the pipe.

ADDITIONAL IMAGES



SEE SECOND PAGE FOR DETAILED SPECIFICATIONS



McELROY

PIT BULL® 26 6" DIPS MAX PIPE SIZE

2" IPS - 6" DIPS (63MM - 180MM)

SPECIFICATIONS

MODELS		POWER		MACHINE DIMENSIONS	
A708502	120V	Minimum Power Requirements	3 kW	Machine Length	15.4" (391.2mm)
A708505	240V			Machine Width	19.7" (500.4mm)
		120V Heater	100-120V, 1,200 Watts, 50 / 60 Hz, 1 Ph	Machine Height	30.4" (772.2mm)
		240V Heater	220-240V, 1,200 Watts, 50 / 60 Hz, 1 Ph	SHIPPING DIMENSIONS	
WEIGHTS		120V Facer	100-120V, 50 / 60 Hz, 1 Ph, 5 Amps	Length	32" (812.8 mm)
Carriage	50 lbs. (22.7 Kg)	240V Facer	220-240V, 50 / 60 Hz, 1 Ph, 7 Amps	Width	40" (1,016 mm)
Heater	14 lbs. (6.4 Kg)	240V Heater Plug type	CEE 7/7 (DIN 49441)	Height	33" (838.2 mm)
Facer	32 lbs. (14.5 Kg)			INCLUDES	
Shipping Weight	130 lbs. (59 Kg)	120V Heater Plug type	NEMA 5-15P		
		240V Facer Plug type	CEE 7/7 (DIN 49441)	Fusion machine, heater, facer, insulated heater stand, facer stand, 6" IPS/DIPS Master insert set and screw /driver kit.	
		120V Facer Plug type	NEMA 5-15P		